



NEW
PRODUCTS 2011

Q-Deck® Timber Decking Landscaping & External Cladding Products



www.qualitydecking.co.uk





Timber Deck Boards

UC3 - treated to Use Class 3
UC4 - treated to Use Class 4

All are manufactured from slow grown and carefully selected softwood.



CAMBRIDGE UC3

20.5mm x 95mm (finished size after machining). This deck board can be used smooth or reeded profile uppermost. Being the thinnest in the range it is the most economical per square metre but please note you need to use more supporting joists - see table on page 61.



NEW


CANTERBURY 2 UC3

27mm x 144mm (finished size after machining). This deck board can be used smooth or grooved side uppermost. Being one of the 2 wider profiles means using fewer deck screws per area. Versatile by design - accepts 2 Q-Grip® Strips. See page 9.



WINCHESTER UC3


27mm x 144mm (finished size after machining). This deck board can be used grooved or ribbed side uppermost. Having a proud profile can marginally improve grip characteristics.



NEW

YORK 2 UC3

33mm x 120mm (finished size after machining). This deck board can be used grooved or smooth side uppermost. As with the 33 x 120mm Multi-purpose board you can use less supporting joists - see table on page 61. Versatile by design - accepts up to 5 Q-Grip® Strips. See page 9.



NEW

PRE-GRIP UC3

27mm x 144mm (finished size after machining). This deck board has 7 grooves - ideal for fitting up to 7 new Q-Grip® Strips. See page 9.

Q-Deck® Deck Boards

Suitable for retro-fitting new **Q-Grip®** Strip.



NEW

Q-DECK® CANTERBURY 2 UC3

27mm x 144mm (finished size after machining).

Accepts 2 **Q-Grip®** Strips.



NEW

Q-DECK® YORK 2 UC3

33mm x 120mm (finished size after machining).

Accepts up to 5 **Q-Grip®** Strips.



NEW

Q-DECK® PRE-GRIP UC3

27mm x 144mm (finished size after machining).

Accepts up to 7 **Q-Grip®** Strips.



7 **Q-Grip®** strips fitted into the **Q-Deck®** Pre-Grip board

NEW

New **Q-Grip®** strip is a versatile retro-fit solution to minimise the risk of slip associated with a slippery deck. It can be fitted to either new grooves made to existing deckboards or to the grooves on new **Q-Deck®** boards detailed above. When used in conjunction with new **Q-Grip®** strip, **Q-Deck® Pre-Grip York 2** and **Canterbury 2** boards allow deck builders to strategically incorporate slip resistant areas within a traditional deck scheme with ease. Areas of decks that tend to require enhanced grip are walkways or boardwalks, borders or edges and steps or stairs.




Q-Grip STRIP™
slip resistant decking

Q-Grip® STRIP UC3

5 x 8 x 1195mm
(finished size after machining).



Fitting **Q-Grip®** strip (see pages 37)



Q-Grip® strip fitted into step edge



Stop Chamfered Components



Stop Chamfered Spindle and Newel*

* Finished with 27 x 120 x 120mm rebated post cap.

NEW
Stop Chamfered
Newel UC3
1500 x 85
x 85mm



NEW Stop
Chamfered
Spindle UC3
41mm x 41mm
x 900mm



NEW

At 1800mm wide, our Stop Chamfered Balustrades are designed to suit most applications but of course they can also be cut to fit narrower gaps between newel posts.



Stop Chamfered Balustrade

UC3 (ready-made)

1800 x 985mm



Pre-Cut Q-Grip®

Our new pre-cut **Q-Grip®** stair treads provide a convenient solution for slip resistant steps and walkways.



◀ Q-Grip® SLIP RESISTANT STAIR TREAD YORK UC3

33 x 120mm
(finished size)
895mm length
1200mm length



▲ Q-Grip® SLIP RESISTANT STAIR TREAD CANTERBURY UC3

27 x 144mm (finished size)
895mm length
1200mm length

Bespoke Q-Grip®

New bespoke anti-slip decking. Due to the awareness and success of **Q-Grip®** decking products we have over the years been asked to consider the manufacture of special/non standard slip resistant decking boards. For sizeable deck projects we can design and produce bespoke **Q-Grip®** slip resistant decking products. Please consult your **Q-Deck®** retailer who will pass the enquiry onto Hoppings Softwood Products for consideration. Bespoke **Q-Grip®** deckboards allow designers to choose the number, position and colour of **Q-Grip®** strips for a particular end use. Different types of timber, such as certified hardwood can also be considered.

Below are descriptions of several examples of bespoke **Q-Grip®** slip resistant deckboards, one of which has been used on a bridge that is to become a major London attraction in 2012.

For more information please visit: www.anti-slip-decking.co.uk

NEW

BESPOKE Q-Grip® LYPTUS HARDWOOD DECKING UC3
20mm x 90mm (finished size after machining).




NEW

BESPOKE Q-Grip® GARAPA HARDWOOD DECKING UC3
19mm x 140mm (finished size after machining).



NEW

BESPOKE Q-Grip® HEAVY DUTY STYLE UC3
44mm x 144mm (finished size after machining).





NEW

Hardwood Deck Boards

Q-DECK® LYPTUS reversible hardwood decking - 20 x 90mm (finished size after machining).



Smooth side.



Reeded/Ribbed side.

Q-Deck® Lyptus hardwood decking is made from cultivated eucalyptus hardwood trees, harvested in less than twenty years, offering unrivalled sustainability.



- Cherry wood appearance
- Darkens to rich walnut-like shades when oiled or wet
- Durable
- Strong
- Tough
- Kiln dried
- Sustainable PEFC certified hardwood




From sustainable plantations in South America.

Design and Construction Advice

- Fit **Q-Deck® Lyptus** over 400mm joists centres.
- Allow 8mm gaps between boards when fitting. Being kiln dried hardwood means you have to allow for some expansion of the boards in the wetter seasons.
- Like many naturally durable timber species, **Q-Deck® Lyptus** is susceptible to staining in contact with iron and moisture. (See page 57 for further information).
- When fixing boards, it is advisable to pre-drill pilot holes with a coated steel drill bit to reduce the chance of the deck screws splitting the timber, especially near the ends of boards. Only use stainless steel deck screws to fix boards.
- Oiling **Q-Deck® Lyptus** with a penetrating deck oil will enhance and darken its appearance and minimise movement due to reduced moisture absorption.
- Clean and re-oil **Q-Deck® Lyptus** annually to rejuvenate its look.
- For more information visit www.hardwood-decking.co.uk



Carpenters Mate® colour coded stainless steel deck screws.





www.qualitydecking.co.uk

www.anti-slip-decking.co.uk

www.timber-cladding.co.uk

www.hardwood-decking.co.uk



Hoppings Softwood Products reserves the right to withdraw products alter product designs or amend fitting instructions without prior notice. For the most up-to-date information it is wise to check at www.qualitydecking.co.uk

® Hickson Decor, Tanalith, Tanalised and Ensele are registered trademarks of Arch Timber Protection.

® DeckMark is a registered trademark of the Timber Decking Association.

© FSC Trademark © 1996. Deckorators™ is a trademark of Universal Consumer Products, Inc.

® Twinson is a trademark of Deceuninck, NV™ Simpson Strong Tie is a trademark of Simpson Strong-Tie Company, Inc.

® Fastenmaster and ® Carpenter's Mate are trademarks of OMG, Inc. © PEFC – The PEFC Council



BMT-PEFC/16-37-56